

# Honeywell®

## Voyager 1202g, wireless scanner, USB, black

Honeywell's Voyager™ 1202g single-line laser scanner incorporates the freedom of Bluetooth® wireless technology. Voyager 1202g delivers the aggressive linear bar code scanning that users have come to expect from the world-renowned Voyager family of scanners.

### Product Highlights of 1202g Bar Code Scanner



- for proper functionality of the product and a full charge readers should buy feed **1202-ZDROJ**
- Bluetooth® Wireless Technology: Facilitates scanning of all standard 1D bar codes 10 meters (33 feet) or more away from the base, depending on the user's environment
- Long Battery Life and Tool-Free Battery Removal: The user-preferred Lithium ion battery provides 12 hours or more of use, depending on scanning volume, and the field-replaceable battery can be exchanged quickly and easily, without the use of tools
- Automatic Interface Configuration: Supports all popular interfaces in one device, replacing the time consuming process of scanning programming bar codes with automatic interface detection and configuration
- Excellent Poor Quality Code Reading: Increases throughput and reduces the potential for hand-keyed errors by quickly scanning a variety of 1D bar codes, including those that are damaged or smudged
- Paging Functionality: Simply press the button on the base to locate your lost scanner; Voyager 1202g responds with a series of beeps and blinking lights on its indicator panel
- Remote MasterMind™ Ready: Reduces total cost of ownership by providing a turnkey remote device management solution that easily manages and tracks usage of installed devices

YOUTUBE='4zPPonJyplY'



# Technical Description

## Functionality & Operation

1D Barcode Symbologies All standard one-dimension barcodes

Communication interface Multi-interface - RS232/KBW/USB

Wireless communication Bluetooth®

WPAN Features Bluetooth® Class II compliance v2.1

## Optical

Maximal skew angle 60°

Depth of scan field 0-367 mm

Bar code scanner Laser

Scanning rate 100scan/s

## Electrical

Battery charging time 4hod

Main battery pack operating time 12hod

Main battery pack Li-Ion 1800 mAh

## Mechanical

Weight 365g

Dimensions Width: 180mm, Height: 92mm Length: 66mm

## Environment

Ingress protection IP42

Shock resistance drop from 1,5 m onto concrete surface

Storage temperature -5 to 35°C

Storage humidity (non-condensing) 0 to 95%

Operating temperature 5 to 40°C

Maximal ambient light 70lux

## Others

Warranty 3 years

## CODEWARE, s.r.o.

Jaromírova 484/37  
120 00 Praha 2 - Nusle  
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444  
codeware@codeware.cz  
<https://www.codeware.cz/>

