

Honeywell®

Voyager 1202g, wireless scanner, USB, black - demonstration unit

Demonstration unit in non-original box. Fully functional, used very rarely.

Product Highlights of 1202g Bar Code Scanner



- for proper functionality of the product and a full charge readers should buy feed **1202-ZDROJ**
- Bluetooth® Wireless Technology: Facilitates scanning of all standard 1D bar codes 10 meters (33 feet) or more away from the base, depending on the user's environment
- Long Battery Life and Tool-Free Battery Removal: The user-preferred Lithium ion battery provides 12 hours or more of use, depending on scanning volume, and the field-replaceable battery can be exchanged quickly and easily, without the use of tools
- Automatic Interface Configuration: Supports all popular interfaces in one device, replacing the time consuming process of scanning programming bar codes with automatic interface detection and configuration
- Excellent Poor Quality Code Reading: Increases throughput and reduces the potential for hand-keyed errors by quickly scanning a variety of 1D bar codes, including those that are damaged or smudged
- Paging Functionality: Simply press the button on the base to locate your lost scanner; Voyager 1202g responds with a series of beeps and blinking lights on its indicator panel
- Remote MasterMind™ Ready: Reduces total cost of ownership by providing a turnkey remote device management solution that easily manages and tracks usage of installed devices

YOUTUBE='4zPPonJypIY'



Technical Description

Functionality & Operation

1D Barcode Symbolologies	All standard one-dimension barcodes
Communication interface	Multi-interface - RS232/KBW/USB
Wireless communication	Bluetooth®
WPAN Features	Bluetooth® Class II compliance v2.1

Optical

Maximal skew angle	60°
Depth of scan field	0-367 mm
Bar code scanner	Laser
Scanning rate	100scan/s

Electrical

Battery charging time	4hod
Main battery pack operating time	12hod
Main battery pack	Li-Ion 1800 mAh

Mechanical

Weight	365g
Dimensions	Width: 180mm, Height: 92mm Length: 66mm

Environment

Ingress protection	IP42
Shock resistance	drop from 1,5 m onto concrete surface
Storage temperature	-5 to 35°C
Storage humidity (non-condensing)	0 to 95%
Operating temperature	5 to 40°C
Maximal ambient light	70lux

Others

Warranty	3 years
----------	---------

CODEWARE, s.r.o.
Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

