



# Honeywell®

## Hyperion 1300g imager, scanner only, black

Featuring an ideal balance of performance, durability and ergonomics, the Hyperion 1300g linear-imaging CCD scanner provides years of hassle-free scanning, especially in scan-intensive or light industrial applications.

Key Features:



Superior Hand-Held Scanning: Increases throughput by offering intuitive and aggressive hand-held scanning performance

Highly Versatile: Eliminates the need to purchase specialty scanners by providing the ability to read out to 18 inches (457 mm) on 13 mil bar codes, as well as reading of high density bar codes

Class-Leading Durability: Increases up time and reduces service costs with a reliable design

Comfortable, Ergonomic Design: Ensures operator comfort and productivity with a gun-shaped form factor optimized for intensive hand-held scanning

Automatic Interface Detection: Supports all popular interfaces in one device, replacing the time consuming process of scanning programming bar codes with automatic interface detection and configuration

Remote MasterMind® Scanner Management Software: Provides a quick and convenient solution for IT administrators seeking to manage all scanners within their network from a single remote location



# Technical Description

## Functionality & Operation

1D Barcode Symbolologies	All standard one-dimension barcodes
--------------------------	-------------------------------------

Communication interface	Multi-interface - RS232/KBW/USB
-------------------------	---------------------------------

## Optical

Depth of scan field	0-367 mm
---------------------	----------

Scanning rate	100scan/s
---------------	-----------

Minimum symbol contrast	20%
-------------------------	-----

Maximal skew angle	60°
--------------------	-----

Bar code scanner	Linear CCD Imager
------------------	-------------------

## Electrical

Power Source	+5 VDC ±5%
--------------	------------

Power Consumption - Standby	125mA
-----------------------------	-------

Power Consumption - Operation	200mA
-------------------------------	-------

## Mechanical

Color	black, ivory
-------	--------------

Weight	160g
--------	------

Dimensions	Width: 112mm, Height: 79mm Length: 150mm
------------	--

## Environment

Storage temperature	-40 to 60°C
---------------------	-------------

Shock resistance	drop from 1,5 m onto concrete surface
------------------	---------------------------------------

Operating temperature	0 to 50°C
-----------------------	-----------

Ingress protection	IP41
--------------------	------

Operating humidity (non-condensing)	0 to 95%
-------------------------------------	----------

## Others

Optional accessories	stand
----------------------	-------

Warranty	5 years
----------	---------

**CODEWARE, s.r.o.**  
Jaromírova 484/37  
120 00 Praha 2 - Nusle  
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444  
codeware@codeware.cz  
<https://www.codeware.cz/>

