

Honeywell®

1472g Voyager XP upgradeable area-imaging wireless scanner, DRH

Honeywell Voyager Extreme Performance (XP) 147x is the next generation of Honeywell handheld sensors, designed for in-store retail environments. The Voyager XP 147x scanner offers highly accurate scan performance, easily capturing damaged and difficult-to-read codes. Scanner corresponds to the new Tobacco Directive - reads DotCode.

With better durability and a more powerful scan capability than previous models the Voyager XP 147x scanner is the perfect option for workflows that include 1D and 2D barcode reading and require a more robust and reliable solution. The scanner's extended scan distance will reach right to the bottom of the cart without bending and wasted time at the checkout. The Voyager XP 147x scanner is fully backward-compatible with existing Voyager accessories, reducing total cost of ownership.



Key features:

- more powerful scan capability than previous models
- easily reads even difficult-to-read and damaged codes
- scanning barcodes up to 30 m from the base
- fully backward-compatible with existing Voyager accessories
- great price/performance ratio
- reads DotCode - 2D version

YOUTUBE='tf1CfDbj2l0'



Technical Description

Functionality & Operation

1D Barcode Symbolologies	All standard one-dimension barcodes
2D Code Symbolologies	all standard 2D-Codes
Communication interface	USB
Indicators	2x LEDs, beeper
Wireless communication	Bluetooth®
WPAN Features	2.4 GHz to 2.5 GHz (ISM Band), Adaptive Frequency Hopping, Bluetooth v4.2, 30 m

Optical

Depth of scan field	5 - 400 mm
Bar code scanner	2D Imager

Electrical

Main battery pack	Li-Ion 2400 mAh
Battery charging time	4.5hod
Main battery pack operating time	14hod

Mechanical

Color	black
Dimensions	Width: 62mm, Height: 173mm Length: 82mm
Weight	210g

Environment

Ingress protection	IP42
Maximal ambient light	100000lux
Shock resistance	Withstands 30 drops from 1,8 m onto concrete surface, 1000 tumbles at 50 cm
Operating humidity (non-condensing)	0 to 95%
Electrical static discharge	±8kV contact, ±15kV air
Operating temperature	5 to 40°C Charging, 0-50°C Non-Charging

Others

Warranty	3 years
----------	---------

CODEWARE, s.r.o.
Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

