



1500P RS232: CCD scanner, black + RS232 cable

Fast and ergonomically advanced compact barcode scanner with auto-sense 3in1 stand.

CipherLab 1500 barcode scanner (linear imager) raises the standard of performance, style and affordability. An incredibly comfortable design and the innovative three-way stand makes it easy to use all day long. A large LED and the adjustable tone ensure instant scan recognition that speeds up the workflow. No moving parts and CipherLabs reputation for reliability mean ultra-low maintenance, giving you remarkably low total cost of ownership. And a five-year warranty guarantees years of worry-free service. The CipherLab 1500 delivers where reliability, durability, comfort, speed, safety, and value matter.



You can easily configure the 1500 scanner with the ScanMaster software.

Bar code scanner CipherLab 1500 is available also in special design for health institutions, pharmacies, and similar social institutes. The housing is cast from a mixture of antibacterial solution developed for this purpose by [Microban](#) corporation.

Autosense, 3-in-1 stand

Autosense

Desktop

Wall mount

Referential customers

Ministry Of Labor And Social Affairs, Czech (hundreds of scanners)

Gesto Computers, spol. s r.o., Czech



Technical Description

Functionality & Operation

| | |
|--------------------------|---|
| 1D Barcode Symbolologies | Codabar, Code 128, Code 39, Code 93, EAN 13/UPCA, EAN 8, French Pharma Code, Industrial 2 of 5, Interleaved 2 of 5, Italy Pharma Code, Matrix 2 of 5, MSI, Plessey, Telepen, UPCE, and others |
| Programmable features | Data editing, interface selection, symbology, configuration |
| Configuration | by programming barcodes, ScanMaster utility |
| Communication interface | USB, USB-HID, USB-VCP, RS232 |

Optical

| | |
|---------------------|-----------------------|
| Bar code scanner | CCD 2500 px |
| Minimal PCS value | 30% |
| Light source | visible red LED 625nm |
| Resolution | 3 mil |
| Depth of scan field | 40-400 mm |
| Maximal skew angle | 70° |
| Maximal pitch angle | 70° |
| Scanning rate | 520scan/s |

Electrical

| | |
|-------------------------------|---------------------|
| Power Consumption - Standby | 350mA |
| Power Consumption - Operation | 170mA , max. 250 mA |

Mechanical

| | |
|--------|-------|
| Weight | 145g |
| Color | black |

Environment

| | |
|-------------------------------------|---------------------------------------|
| Maximal ambient light | 100000lux |
| Ingress protection | IP30 |
| Operating temperature | 0 to 50°C |
| Storage temperature | -20 to 60°C |
| Operating humidity (non-condensing) | 10 to 90% |
| Storage humidity (non-condensing) | 5 to 95% |
| Shock resistance | drop from 1,5 m onto concrete surface |
| Electrical static discharge | ±8kV contact ±15kV air |

CODEWARE, s.r.o.

Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

