



1502 Kit USB: Laser Bar Code Reader with stand, black, USB-HID

Fast and ergonomically advanced compact laser barcode scanner with optional 3in1 stand.

Lightweight and ergonomic, this laser scanner enables workers to capture critical data from 2 to 57 cm away quickly, accurately, and comfortably shift after shift in any work environment.



Together with its build test-proven to survive 1.2 m drops onto concrete the 1502 makes one reliable and valuable choice for laser scanning.

Main Highlights Of CipherLab 1502 Laser Bar Code Scanner

able to read barcode from 2 to 57 cm (0.8 to 22.4 in.) away

lightweight, ergonomic design for repetitive use

innovative 3-in-1 handsfree scanning, desktop, or wall mount stand for easy scanning

test-proven to withstand 1.2 m (3.9 ft.) multiple drops from concrete

supports multiple languages and symbologies for worldwide applications

widely programmable ScanMaster software included free with purchase for data editing support, interface selection, and symbology configuration

Innovative 3 in 1 Stand

Handsfree scanning

Desktop holder

Wallmount type



Technical Description

Functionality & Operation

1D Barcode Symbolologies	Codabar, Code 128, Code 39, Code 93, EAN 13/UPCA, EAN 13/UPCA + ADDON 2, EAN 13/UPCA + ADDON 5, EAN 8, EAN 8 + ADDON 2, EAN 8 + ADDON 5, French Pharma Code, GS1 Data Bar (RSS), Industrial 2 of 5, Interleaved 2 of 5, Italy Pharma Code, Matrix 2 of 5, MSI, Plessey, Telepen, UCC/EAN-128, UPCA, UPCA + ADDON 2, UPCA + ADDON 5, UPCE, UPCE + ADDON 2, UPCE + ADDON 5
Programmable features	Data editing, interface selection, symbology, configuration
Configuration	by programming barcodes, ScanMaster utility
Language support	Belgian, French, German, Italian, Japanese, Norwegian, Portuguese, Spanish, Swedish, US and UK English, Turkish

Optical

Light source	visible laser diode VLD 650 nm
Bar code scanner	Laser
Resolution	4 mil
Depth of scan field	20-570 mm
Maximal pitch angle	65°
Maximal skew angle	50°
Scanning rate	100scan/s

Electrical

Power Source	+5V ±10%
Power Consumption - Standby	35mA
Power Consumption - Operation	210mA

Mechanical

Dimensions	Width: 153cm, Height: 61cm Length: 93cm
Weight	149g
Color	black

Environment

Maximal ambient light	100000lux
Operating temperature	0 to 50°C
Storage temperature	-20 to 60°C
Operating humidity (non-condensing)	10 to 90%
Storage humidity (non-condensing)	5 to 95%

CODEWARE, s.r.o.

Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

