



1560P Kit USB: Wireless Linear Imager + Cradle + USB Cable, worn, used one, Bluetooth

Used but fully functional 1560 Wireless Barcode Scanner (Linear Imager). 90-meter Bluetooth signal range, sophisticated design and a multi-purpose communication stand that can operate up to seven handheld bar code scanners at the same time.

CipherLab 1560 scanner raises the standard of performance, style and affordability. An incredibly comfortable design and the innovative three-way stand make it easy to use all day long. A large LED and the adjustable tone ensure instant scan recognition that speeds up the workflow. No moving parts and CipherLabs reputation for reliability mean ultra-low maintenance, giving you remarkably low total cost of ownership. And a five-year warranty guarantees years of worry-free service. The CipherLab 1560 delivers where reliability, durability, comfort, speed, safety, and value matter.



You can easily configure the 1560 scanner with the ScanMaster software.

Scanning options:

- trigger
- Auto-sense
- continuous mode

Adjustable stand:

- desk stand
- wall mount
- auto-sense stand



Technical Description

Functionality & Operation

Language support	Japanese, French, German, Italian, Norwegian, Portuguese, Spanish, Swedish, US and UK English, Belgian, Turkish, Hungarian
Signal coverage	90m
Bluetooth profiles	HID, SPP
1D Barcode Symbolologies	Codabar, Code 128, Code 39, Code 93, EAN 13/UPCA, French Pharma Code, Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, MSI, Plessey, Telepen, and others
Programmable features	Data editing, interface selection, symbology, configuration
Communication interface	Bluetooth® Class 2 (2.4 GHz)Version 4.0+EDR
Configuration	by programming barcodes

Optical

Bar code scanner	CCD 2500 px
Light source	red LED 618-626 nm
Resolution	3 mil
Depth of scan field	40-400 mm
Maximal pitch angle	70°
Maximal skew angle	70°
Minimal PCS value	25%
Scanning rate	520scan/s

Electrical

Main battery pack operating time	36hod measured for 1 scan / 5 sec
Power Source	+5V ±10%
Power Consumption - Operation	250mA
Power Consumption - Standby	20mA

Mechanical

Weight	173g
Color	black

Environment

Maximal ambient light	100000lux
Operating temperature	0 to 50°C

CODEWARE, s.r.o.

Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

