



2564ER Extended range Rugged Wireless 2D-code scanner, long DOF with tether plate + Cradle + USB Cable, Bluetooth

With raising demands for advanced scanning abilities in many industries, such as retail, warehousing and light industry, CipherLab has attentively designed the durable 2500 series handheld scanner to suit various applications in harsh environments. CipherLab 2500 series is able to deliver superior scanning abilities to speed up the efficiency of data collection. Along with business-rugged durability, its high performance is well protected so users can enjoy fast workflow without any worries. Moreover, the 2500 series is also equipped with additional user friendly features to create a productive experience for its users. Wireless barcode scanner allows you to scan a barcode and transfer data up to a distance of 100 m from the base.

The CipherLab 2564ER series business-rugged handheld scanner takes performance up a notch with a 55 scan rate for fast operations. Along with the ability to read high-density 1D and 2D barcodes and low contrast barcodes as low as 25%, the CipherLab 2500ER series eases its aiming for scanning excellence on tiny objects or the barcodes which are poorly printed. CipherLab 2500 series equips with a scan beam of 3 mm in width from 15 cm away that allows users to reduce the probabilities of misreads while barcodes are placed close to each other. The CipherLab 2500 series handheld scanner maximizes workforce productivity for everyday operations in a variety of business.



Key features of the Cipherlab A2564ER 2D code industrial scanner

Bluetooth v4.0 Dual Mode with EDR

IP65 rating and 1.8 m/ 6 ft. drop resistance

Snappy 55 scan rate and 15% PCS

Auto detection of USB, RS232 and keyboard wedge interface

Swappable battery runs up to 24 hours on single charge

ESD Protection ± 10 kV(contact), ± 20 kV (air)

[Web-based ScanMaster setup tool](#) for easy access and configuration



Technical Description

Functionality & Operation

2D Code Symbolologies	MicroPDF417, Composite codes, TLC-39, PDF417, HanXin Code, GS1 DataMatrix, GS1 QR Code, Data Matrix, QR code, Micro QR Code, Aztec, MaxiCode
1D Barcode Symbolologies	All standard one-dimension barcodes
Wireless communication	Bluetooth®
WPAN Features	Bluetooth® v4.0

Optical

Resolution	1280 x 800 px
Light source	visible red LED 660 nm
Depth of scan field	7.62 cm ~ 1778 cm
Scanning rate	30 fps ~ 55 fps
Bar code scanner	Advanced Long 2D Imager
Resolution	1D: 3 mil / 2D: 5 mil
Minimal PCS value	25%
Maximal skew angle	60°
Maximal pitch angle	60°

Electrical

Main battery pack operating time	24hr
Main battery pack	Rechargeable Li-Ion battery 3000 mAh, 3.7V

Mechanical

Weight	320.3g
Color	black, yellow
Dimensions	Width: 66mm, Height: 160.5mm Length: 98.2mm

Environment

Maximal ambient light	100000lux
Operating temperature	0 to 50°C
Storage temperature	-40 to 70°C
Operating humidity (non-condensing)	10 to 90%
Storage humidity (non-condensing)	5 to 95%
Ingress protection	IP65

CODEWARE, s.r.o.

Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

