

## CPT-8231-C Portable Terminal, CCD, WLAN & BT, 4 MB, without cradle

The 8200 series Portable Data Terminal is the smallest and the cheapest one, even with the high performance designed for all-day, everyday use. Like all portable terminals from CipherLab, it is supported by a rich set of development tools, including a "C" and "Basic" compilers. With its integrated barcode scanning unit, the 8200 Portable Data Terminal is ideal for applications such as inventory control, access control and shop floor management, etc.

The device has got features, which definately assure you about CipherLab CPT-8200 / CPT-8231 is the best choice for your retail application:



- long-lasting power performance for continuous productivity. CPT-8200 runs on a rechargeable Li-ion battery - for more than 124 continuous hours between charges;
- choice of linear imager, laser, or 2D imager barcode scanning - or, if you want it, no barcode scanner;
- sound system is able to play VAW, MP3 files - the device may be easily used for example in storage systems with walking-talking;
- in noisy environment can be set also vibration good read feedback (beside beep and diode flash);
- lightweight, ergonomic form factor that easily fits in your palm and your pocket;
- supports a variety of C and BASIC programming;
- CipherLab Application Generator enables custom applications;
- MicroSD card slot with SDHC support;
- user-friendly interface and easy-to-read backlit LCD screen;
- large internal memory for user data - up to 8 MBytes;
- optional wireless capability - Bluetooth (WPAN) and/or WiFi (WLAN);

CipherLab portable terminal 8200 is available in the variants:

- CPT-82xx-C with integrated CCD scanner of 1D bar code (linear imager)
- CPT-82xx-L with integrated laser scanner of 1D bar code
- CPT-82xx-2D with integrated 2D Imagerem
- CPT-8200 batch off-line terminal with memory
- CPT-8231 wireless terminal with memory, WLAN and Bluetooth communication



# Technical Description

## Functionality & Operation

|                         |  |
|-------------------------|--|
| WLAN Features           | IEEE 802.11 b/g  |
| Communication interface | RS232, USB-HID, USB-VCP  |
| Indicators              | Dual-color LEDs (red/green, blue/green), vibration, voice  |
| Program memory          | 8MB Flash  |
| Data memory             | 4MB SRAM   |
| Data memory             | 8MB SRAM   |
| Data retention          | 25den  |
| Display type            | LED backlight  |
| Keyboard                | 24 keys, with backlight  |
| Programmable features   | BLAZE C Compiler and BASIC Compiler, FORGE Application Generator, STREAM Wireless studio, MIRROR Terminal Emulator |

## Optical

|                  |            |
|------------------|------------|
| Bar code scanner | CCD        |
| Resolution       | 160x160 px |

## Electrical

|                                  |                       |
|----------------------------------|-----------------------|
| Main battery pack operating time | 124hod                |
| Main battery pack                | Li-Ion 1200 mAh, 3,7V |

## Mechanical

|            |   |
|------------|---|
| Dimensions | Width: 32mm, Height: 58mm Length: 136mm |
| Weight     | 150g                                    |

## Environment

|                                     |   |
|-------------------------------------|---|
| Shock resistance                    | multiply drops from 1,2 m onto concrete surface, 5 drops on each side |
| Ingress protection                  | IP54  |
| Operating temperature               | -10 to 60°C   |
| Storage temperature                 | -20 to 70°C   |
| Operating humidity (non-condensing) | 10 to 90%   |
| Electrical static discharge         | ±8kV contact, ±15kV air   |

## Others

|                      |  |
|----------------------|--|
| Optional accessories | charging and communication cradle, pistol grip, protective cover |
|----------------------|--|

## CODEWARE, s.r.o.

Jaromírova 484/37  
120 00 Praha 2 - Nusle  
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444  
codeware@codeware.cz  
<https://www.codeware.cz/>

