

axicon

6515 verifier 1D codes up to 125mm

The Axicon 6515 barcode verifier has been designed to read linear barcodes with a width of up to 125 mm (4.9") including quiet zones. This means only one verifier is needed to check all your GS1 barcodes - EAN/UPC, ITF-14 and GS1-128 - if the outer case and logistics label barcodes are not at their maximum size. For companies using a 100 mm (4") wide thermal transfer printer for all their outer case barcode labelling, this verifier is perfect. It is used by manufacturers worldwide.

Lightweight and portable, needing only a USB connection. Verifies to ISO/IEC standards, with ANSI reporting as an option. Results are immediately displayed on screen, and reports can be printed or e-mailed for remote diagnosis. Reports may be saved automatically to support ISO 9001 quality control procedures. Designed to function with any PC running any currently supported version of Microsoft Windows, or the Axicon PV-1000 portable display unit. Software is always updated to meet latest requirements of the GS1 General Specifications.



The verifier is supplied as the verifier read-head, its data cable, a CD with the Axicon verifier software (in several languages), a quick start guide, a calibration card and compliance certificates in a protective carry case.

Android App for Axicon verifiers:

Free to use, this app allows anyone with an Axicon 6000, 6500 or 7000 series verifier to use it with an Android device, and record the results as easily as with a PC or laptop. The app can also be used to open the saved scan files, whichever linear barcode verifier has been used to create them.

[Available for download on Google Play.](#)

YOUTUBE='WIZbjFiliCg'



Technical Description

Functionality & Operation

| | |
|--------------------------|--|
| Communication interface | USB |
| 1D Barcode Symbolologies | EAN 13, EAN 8, UPCA, UPCE, GS1-DataBar, ITF-14, GS1 128, Code 39, Code 93, Code 128, Codabar, MSI, Plessey |
| Operating system | Windows, Android |

Electrical

| | |
|--------------|--------------|
| Power Source | 150mA at 5v. |
|--------------|--------------|

Mechanical

| | |
|------------|---|
| Dimensions | Width: 145mm, Height: 113mm Length: 128mm |
|------------|---|

| | |
|--------|------|
| Weight | 675g |
|--------|------|

| | |
|--------------|-----------|
| Body housing | aluminium |
|--------------|-----------|

Environment

| | |
|-----------------------|------------|
| Operating temperature | 10 to 40°C |
|-----------------------|------------|

| | |
|---------------------|-------------|
| Storage temperature | -20 to 70°C |
|---------------------|-------------|

| | |
|-------------------------------------|-----------|
| Operating humidity (non-condensing) | 25 to 80% |
|-------------------------------------|-----------|

| | |
|--------------------|------|
| Ingress protection | IP50 |
|--------------------|------|

Others

| | |
|----------------|--|
| Certifications | CE marking (compliant with RoHS and EMC directives), Compliant with ISO/IEC 15416 and ISO/IEC 15426-1, Can meet the requirements of 21 CFR part 11 |
|----------------|--|

CODEWARE, s.r.o.

Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

