

BD-388III Corded long range CCD

The enhanced linear imager bar code scanner BD-388III offers laser-like and high performance barcode reading: 500 scans/second, 400mm scanning distance for all of barcode reading including EAN 128 code and GS1 data bar.

BD-388III is built with Keyboard, RS232 USB and Wand interface. It supports use replaceable interface cable by RJ45 phone jack; different interface can be interchangeable just by changing cable. It is simplified installation and integration and good to lessen your inventory load.



The scanner is enhanced with Auto Sensor function for hand-free operation to lengthen the optical life. Furthermore, the ergonomic and gun type design body offers maximum comfort for every day use.



Technical Description

Functionality & Operation

Communication interface	USB
1D Barcode Symbolologies	All standard one-dimension barcodes

Optical

Scanning rate	500scan/s
Bar code scanner	CCD

Electrical

Power Source	+5 VDC $\pm$ 5%
--------------	-----------------

Mechanical

Body housing	ABS plastic with rubber
Weight	130g
Dimensions	Width: 90mm, Height: 193mm Length: 85mm

Environment

Maximal ambient light	10000lux
Operating temperature	0 to 50°C
Storage temperature	-20 to 70°C
Operating humidity (non-condensing)	20 to 95%
Shock resistance	drop from 1,2 m onto concrete surface

Others

Warranty	6 months
----------	----------

CODEWARE, s.r.o.
Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

