



# **BM-C02 Mobile POS printer**

Portable, wireless receipt printer and barcode, very small dimensions at a very affordable price, it is Birch BM C02. With its compact size, flexible connectivity and simple operation you can have it always with you, as you and customers will appreciate.

The company offers Birch practical receipt printer very small dimensions and low weight but high battery life per charge battery. On one charge the 8-15hours shift operating at full capacity, or 7 days in standby mode. Particularly suited to the hospitality, kiosk sales apod..Broad range of applications, since it is possible to connect the printer via USB, Bluetooth or RS232. Compatible with Windows, Android and Linux systems. Carrying case in the basic price of the printer.





#### Key features of the printer BM-C02:

- low weight of 0.19 kg
- small dimensions 92.5 x 75.5 x 37 m
- m communication interfaces: USB, Bluetooth, RS2
- 32 large 2000mAh battery life up to 8-15 hours in full operation on a single cha
- rge resistant protective packaging in p
- rice very good
- price Supported operating systems: Android, Windows,
- Linux supported appl<u>ications PEXESO</u>, eÚčtenka,

T

ΕE

#### TA Connecting a Bluetooth printer BM-I02 with Tablet Android E

ET

PEXESO: YOUTUBE='

SS

-xw9fftmQ' Connecting a Bluetooth printer BM-i02 with phone Samsung A3 Android eÚčtenka: YOUTU

ΒE

=

hb5MqxcXEa8' Connecting a Bluetooth printer BM-i02 with phone Samsun

g

A3 Android Teeta:

YOUTUBE='SFtRgmZdu0













## **Technical Description**

### Functionality & Operation

·	
Print mode	direct thermal
Print speed	70mm/sec (3 ips)
Print resolution	203dpi
Communication interface	Bluetooth 2.1, USB, RS232
1D Barcode Symbologies	All standard one-dimension barcodes
Commands set	ESC/POS
Electrical	
Battery charging time	4hod
Main battery pack operating time	8hod
Main battery pack	Rechargeable Li-Ion battery 2000 mAh
Mechanical	
Dimensions	Width: 75mm, Height: 37mm Length: 92mm
Weight	0.19kg without paper roll
Consumables	
Maximal paper width	58mm
Media thickness	0.06 to 0.08mm
Environment	
Operating temperature	0 to 45°C
Storage temperature	-10 to 60°C
Operating humidity (non-condensing)	10 to 80%
Storage humidity (non-condensing)	10 to 90%

CODEWARE, s.r.o. Jaromírova 484/37

120 00 Praha 2 - Nusle IČ: 61061395, DIČ: CZ61061395





