

CP-Q2 POS Receipt Printer with autocutter, USB + RS232, black

Durable, compact, reliable POS receipt printer. Birch CP-Q2 is built with exceptional price/performance ratio in mind, it ensures best-in-class performance and durability.

Birch CP-Q2 POS receipt thermal printer is with its compact size is ideal for smaller counter spaces.



Main features of the Birch CP-Q2 receipt printer

- 3" Direct Thermal POS Printer with Auto Cutter
- Compact Design for Small Counter Space
- Printing Speed up to 200mm/s
- High Resolution of up to 203 dpi
- USB+Serial Combo
- Drop-in Paper Loading



Technical Description

Functionality & Operation

Communication interface	RS232, RJ-11 cash drawer port, USB
Maximal print width	72mm
Print mode	direct thermal
Memory	256kB (NV Flash)
Fonts	13 international character set, Big5 / GB123
Commands set	ESC/POS
Print speed	200mm/sec
1D Barcode Symbolologies	Code 39, Code 93, EAN 128, UPC/EAN/JAN, Interleaved 2 of 5, Codabar
Print resolution	203dpi
Input buffer	64kB

Electrical

Power Source	External adapter, Input: 110~220 VAC 50~60 Hz, Output: DC 24V, 2.5A 60W
--------------	---

Mechanical

Color	black
Dimensions	Width: 140mm, Height: 141.5mm Length: 183mm
Weight	1kg

Consumables

Maximal roll diameter	80mm
Maximal paper width	79.5mm (±0,5 mm)
Media type	roll of thermal paper

Environment

Operating temperature	0 to 45°C
Operating humidity (non-condensing)	10 to 80%
Storage temperature	-10 to 60°C
Storage humidity (non-condensing)	10 to 80%

CODEWARE, s.r.o.
Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

