

DP-2412 Desktop Direct Thermal Bar Code Printer, 5 ips, 203 dpi, USB

DP-2412 is a desktop barcode printer of very small size. It is lightweight and ideal as a portable printer. It has print speed 127 mm / sec, print resolution 203 dpi and easy to connect via USB or cash drawer via RJ-11.



Basic features of barcode printer DP-2412:

- direct thermal printing
- 203 DPI print resolution
- print speed of up to 127 mm/s - 5 ips
- good price
- Memory 4 MB Flash, 4 MD SDRAM
- easy media loading
- RJ-11 plug for cash drawer



Technical Description

Functionality & Operation

1D Barcode Symbolologies	All standard one-dimension barcodes
2D Code Symbolologies	all standard 2D-Codes
Print resolution	203dpi
Print mode	direct thermal
Print speed	127mm/sec
Fonts & barcode rotation	0°, 90°, 180°, 270°
Memory	4MB Flash
Memory	4MB DRAM
Graphics	BMP, PCX
Communication interface	USB, RJ-11 cash drawer connector for POS printer

Optical

Sensors	open print-head detector, transmissive
---------	--

Electrical

Power Source	External adapter 12V 3A 36W
--------------	-----------------------------

Mechanical

Dimensions	Width: 135mm, Height: 137mm Length: 190mm
Weight	1.04kg
Body housing	double-walled plastic
Color	black

Consumables

Maximal paper width	60mm
Media type	thermal labels, continuous, fan-fold, notch
Minimal paper width	20mm
Maximal roll diameter	80mm

Environment

Operating temperature	5 to 45°C
Storage temperature	-40 to 55°C
Operating humidity (non-condensing)	20 to 80%

CODEWARE, s.r.o.
Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

