

## ≡ OPTICON

### C-41S Manual linear CCD barcode reader, USB, black

This lightweight and ergonomically shaped device fits comfortably in anyone's hand, making it suitable for all-day scanning applications.

Opticon awards the user with [a free worldwide accessible setup tool](#) as an addition to the standard way of setting up the device using a printed barcode manual.



The C-41S is a durable CCD scanner with a wide optical window. With its aggressive scan engine the C-41S operates at a speed of 300 scans per second. This lightweight scanner fits on every desk.

This lightweight and ergonomically shaped device fits comfortably in anyone's hand, making it suitable for all-day scanning applications.

The C-41S is available with a USB interface and is easily programmable to suite your application.

Opticon C41-S CCD Barcode Scanner Unboxing:

YOUTUBE='2cKAdDcd\_Tw'



# Technical Description

## Functionality & Operation

1D Barcode Symbolologies	All standard one-dimension barcodes
--------------------------	-------------------------------------

Communication interface	USB
-------------------------	-----

## Optical

Depth of scan field	40-90 mm
---------------------	----------

Scanning rate	300scan/s
---------------	-----------

Bar code scanner	CCD 1500 px
------------------	-------------

Light source	visible red LED 650 nm
--------------	------------------------

## Electrical

Power Source	100-240V, 50-60Hz
--------------	-------------------

## Mechanical

Weight	55g
--------	-----

Dimensions	Width: 55.9mm, Height: 154mm Length: 33.8mm
------------	---

## Environment

Shock resistance	drop from 1,5 m onto concrete surface
------------------	---------------------------------------

Vibrations resistance	10-100 Hz with 2G for 1h.
-----------------------	---------------------------

Operating temperature	0 to 50°C
-----------------------	-----------

Storage temperature	-20 to 60°C
---------------------	-------------

Operating humidity (non-condensing)	5 to 95%
-------------------------------------	----------

Storage humidity (non-condensing)	5 to 95%
-----------------------------------	----------

Maximal ambient light	10000lux
-----------------------	----------

Ingress protection	IP42
--------------------	------

## Others

Certifications	CE, FCC, VCCI, RoHS, IEC 62471 Exempt
----------------	---------------------------------------

## CODEWARE, s.r.o.

Jaromírova 484/37  
120 00 Praha 2 - Nusle  
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444  
codeware@codeware.cz  
<https://www.codeware.cz/>

