

Honeywell®

Honeywell CK70 Industrial mobile computer, 2D, RFID, Wi-Fi, VGA, GPS, 3G, WEH, large keys

Intermec CK70 is a rugged, yet stylish wireless mobile computer. Also included is a fully integrated UHF RFID reader without visible external antenna. This revolutionary terminal offers easier tight integration into existing application solutions. Flexible wireless technology provides optimal network coverage. Powerful processor Texas Instruments OMAP3 offers with lower energy consumption higher performance, speed and reliability you CK70 can rightly expect.

Terminal CK70 is characterized by ease of operation. It is the ideal assistant for logistics. It is up to 12% smaller and lighter compared to other devices in the same class. It focuses on increasing efficiency and unmatched reliability even in the most extreme conditions. With a scan speed of 12.7 m / s for virtually all lighting conditions suited to highly dynamic environment. Integrated Client Intermec CK70 ScanNGo allows users to configure and automatically download software applications in seconds instead of minutes. Exceptional battery life, blurring the downtime at work. Sufficiently large keypad can be easily operated even with work gloves.



Main features CK70:

- IP67
- ergonomic design
- large keyboard
- powerful 2D imager
- Longlife battery
- multi-core processor
- r reading RFID ta
- gs 3.5 "VGA touchscr
- een 5 Mpix ca
- mera Intermec client



Technical Description

Functionality & Operation	
Communication interface	IrDA, USB Host, USB Client
1D Barcode Symbologies	All standard one-dimension barcodes
Memory	512MB DRAM, 1GB Flash
2D Code Symbologies	all standard 2D-Codes
Display type	3,5" VGA color, with backlight
Operating system	Windows® Embedded Handheld
Expansion slot	Micro SD Card (SDHC)
RFID transponder protocols	ISO 18000-6C
Frequency	UHF: 865 - 868 MHz (EU)
Touch-screen panel	Yes
WLAN Features	IEEE 802.11 a/b/g/n
Antennas, Antenna inputs	internal
WPAN Features	Bluetooth® Class II v2.1 EDR
Optical	
Bar code scanner	2D Imager
Camera	5 MPix, with Autofocus, with LED flash
Electrical	
Main battery pack	Rechargeable Li-Ion battery 5200 mAh, 3,7V
Mechanical	
Dimensions	Width: 80mm, Height: 43mm, Length: 237mm
Weight	562g
Environment	
Operating temperature	-20 to 60°C
Storage temperature	-30 to 70°C
Shock resistance	multiply drops from 2,4 m onto concrete surface
Storage humidity (non-condensing)	0 to 95%
Electrical static discharge	±8kV contact, ±15kV air
Ingress protection	IP67

CODEWARE, s.r.o.
Jaromirova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
+420 737 274 952
codeware@codeware.cz
<https://eshop.codeware.cz/>

