

Honeywell®

ScanPal EDA71 - rugged tablet 1D/2D, Android, WLAN

Honeywell ScanPal EDA71 is an update of the popular EDA70 tablet, an elegant, lightweight, 7" robust mobile tablet, ideal for workflows requiring intense scanning, reliable communication and information access, and seamless processing of multiple tasks. Support for Android™ O, P, and Q provides long-term availability of the security updates that are necessary for long product life.

Honeywell's ScanPal EDA71 is a rugged, enterprise-class 7" tablet computer delivering real-time connectivity, fast data capture capabilities and enterprise levels of reliability and protection.



The ScanPal EDA71 features a powerful new processor platform, 1D/2D barcode scanning and a built-in 13Mpx camera, plus enough battery life to last a full shift and beyond, keeping mobile workers always connected to crucial information to place orders, check stock, look up order status or scan items as they are removed for delivery.

Key featured:

- Support for Android™ O, P, and Q
- Easy To Use Integrated Barcode Scanning
- Large Touchscreen Display high durability, can be used even with wet hands
- Built For Rugged Environments IP64
- Compatible with all existing ScanPal EDA70 tablet accessories



Technical Description

Functionality & Operation

Wireless communication	Bluetooth®, WiFi, NFC
Expansion slot	Micro SD Card (SDHC)
Display type	7" HD 1280x720px, bright color LCD with backlight
Operating system	Android
Touch-screen panel	capacitive multi-touch
Audio	speaker , Bluetooth wireless headset support
GPS navigation	BeiDou, a-GPS, GLONASS, GPS
WLAN Features	IEEE 802.11 a/b/g/n/ac
Memory	2GB RAM, 32GB Flash
CPU Type	1.8 GHz Qualcomm SDM450 8-core
Operation interface	ON/OFF, scan button, color touch LCD panel, volume up and down keys

Optical

Sensors	light sensor, proximity sensor, accelerometer
Bar code scanner	2D Imager
Camera	13 MPix

Electrical

Main battery pack	Rechargeable Li-Ion battery 4000 mAh, 3,8V
-------------------	--

Mechanical

Dimensions	Width: 118mm, Height: 21mm Length: 214mm
Weight	550g

Environment

Operating temperature	-10 to 50°C
Storage temperature	-20 to 70°C
Operating humidity (non-condensing)	10 to 90%
Ingress protection	IP64
Shock resistance	200 tumbles at 0,5 m, multiply drops from 1,2 m onto concrete surface
Electrical static discharge	±12kV air, ±8kV contact

Others

CODEWARE, s.r.o.
Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

