



Honeywell 1350G, 2D imager, multi-interface, USB kit, black

Voyager 1350g is designed to fulfill different customers' scanning needs in various applications, for both printed and digital codes, 1D, Datamatrix or DotCode, regardless of the application where used. The Voyager 1350g can read them all effortlessly. Intelligent software tools simplify scanner setup and installation and facilitate integration with other devices.

Flexibility and Versatility



Voyager 1350g is designed to fulfill different customers' scanning needs in various applications, for both printed and digital codes, 1D, Datamatrix or DotCode, regardless of the application where used. The Voyager 1350g can read them all effortlessly.

Reliable Performance

Equipped with Honeywell's decoding technology, the Voyager 1350g offers reliable performance on a wide variety of popular barcodes. This includes damaged codes which helps avoid errors associated with manually entering data; saving time and improving productivity.

Intelligent Software Tools

The Voyager 1350g is supported by Honeywell's EZ Config, OPOS/JPOS drivers, POSNET4, SMU and plug-ins. These intelligent software tools greatly simplify the setup and installation of the 1350g and makes integration with other equipment easy.



Technical Description

Functionality & Operation

1D Barcode Symbolologies	All standard one-dimension barcodes
--------------------------	-------------------------------------

2D Code Symbolologies	all standard 2D-Codes, DotCode
-----------------------	--------------------------------

Communication interface	USB
-------------------------	-----

Optical

Minimal PCS value	25%
-------------------	-----

Bar code scanner	2D Imager , 1280 x 800px
------------------	--------------------------

Electrical

Power Source	Input Voltage: 5 ± 0.5VDC, Operating Power: 2 W (400 mA @ 5V DC), Standby Power: 0.55 W (110 mA @ 5V DC)
--------------	--

Mechanical

Dimensions	Width: 125mm, Height: 154mm Length: 72.5mm
------------	--

Weight	130g
--------	------

Environment

Operating temperature	0 to 50°C
-----------------------	-----------

Storage temperature	-40 to 60°C
---------------------	-------------

Electrical static discharge	±15kV air, ±8kV contact
-----------------------------	-------------------------

Operating humidity (non-condensing)	0 to 95%
-------------------------------------	----------

Shock resistance	250 tumbles at 0,5 m, drop from 1,2 m onto concrete surface
------------------	---

Ingress protection	IP40
--------------------	------

Maximal ambient light	100000lux
-----------------------	-----------

Others

Warranty	3 years
----------	---------

CODEWARE, s.r.o.

Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

