

Honeywell®

Granit 1981i - wireless industrial-grade Area-Imaging scanner, USB kit

Granit 1981i is capable of reading both 1D and 2D barcodes across a wide range of distances. From poor quality 2 mil codes scanned at close range to 100 mil codes hanging from warehouse rafters scanned at ranges of 16 m, the Granit series is built to perform. With Bluetooth® technology, you have complete freedom of movement up to 100 m (328 ft) from the base.

With an unmatched range and the option of wireless freedom, Granit scanners maximize operator productivity in the harshest environments.



Key featured:

- Robust design with protection rating IP65
- Outstanding scan performance on poor quality and damaged barcodes
- Reading barcodes across a wide range of distances
- With Bluetooth® technology range up to 100 m from base

Honeywell Granit Durability Test

YOUTUBE='kgnqVAzd0XA'















Technical Description

Functionality & Operation	
Communication interface	keyboard, RS232, USB
1D Barcode Symbologies	All standard one-dimension barcodes
2D Code Symbologies	all standard 2D-Codes
WPAN Features	Adaptive Frequeny Hopping Bluetoth® v2.1, Class 1, 100m line of sight
Optical	
Depth of scan field	10 - 1600 cm
Minimum symbol contrast	30% 1D, 40% 2D
Bar code scanner	2D Imager
Resolution	2 mil
Electrical	
Main battery pack	Li-lon 2400 mAh
Main battery pack operating time	8hod
Battery charging time	4.5hod
Mechanical	
D: .	
Dimensions	Width: 75mm, Height: 133mm Length: 195mm
Weight	Width: 75mm, Height: 133mm Length: 195mm 420g
Weight	
Weight Environment	420g
Weight Environment Operating temperature	420g -20 to 50°C
Weight Environment Operating temperature Storage temperature	420g -20 to 50°C -40 to 70°C
Weight Environment Operating temperature Storage temperature Operating humidity (non-condensing)	420g -20 to 50°C -40 to 70°C 0 to 95%
Weight Environment Operating temperature Storage temperature Operating humidity (non-condensing) Shock resistance	420g -20 to 50°C -40 to 70°C 0 to 95% Withstands 50 drops from 2 m onto concrete surface, 5000 tumbles at 1m
Weight Environment Operating temperature Storage temperature Operating humidity (non-condensing) Shock resistance Ingress protection	420g -20 to 50°C -40 to 70°C 0 to 95% Withstands 50 drops from 2 m onto concrete surface, 5000 tumbles at 1m IP65

Warranty 3 years

CODEWARE, s.r.o. Jaromírova 484/37 120 00 Praha 2 - Nusle IČ: 61061395, DIČ: CZ61061395





