

Honeywell°

Honeywell ScanPal EDA61K - NUM, WLAN, 3G/32G, SR, camera, Android, GMS, prelicensed Software Client Pack

The robust Android mobile computer Honeywell ScanPal EDA61K with a 4" multi-touch display was specifically designed for the demanding work environments in warehousing, logistics and retail. The powerful Qualcomm SDM450 1.8 GHz octa-core processor and 3 GB of RAM and 32 GB of flash memory ensure top performance in every task. The mobile computer's powerful 7,000 mAh hot-swappable battery lasts up to three shifts. Plus, thanks to its ergonomic, well-balanced design and low weight of only approximately 460 grams, you carry the mobile computer comfortably all day long.

The ScanPal EDA61K is also equipped with a 13 megapixel camera with auto-focus and interfaces for Wi-Fi (802.11ac), Bluetooth 4.2, USB-C, GPS and LTE. The mobile computer is available with either a numeric (34 keys) or an alphanumeric keyboard (47 keys). Also, various scan engines ensure a fast and precise reading range within a few centimeters up to 15 meters. In accordance with IP65, the ScanPal EDA61K is also very durable.



The mobile computers are offered with one-year pre-licensed packages in two versions. The Software Client Pack includes Basic TE, SmartTE, Enterprise Browser and Launcher, 1 Year Software Maintenance. Device Client Pack includes Basic TE, Enterprise Browser and Launcher, 1 Year Software Maintenance.

Key features:

- high capacity battery s Hot Swap
- durability IP65
- light and ergonomic design
- prelicensed software packages



Technical Description

Functionality & Operation

Functionality & Operation	
Wireless communication	Bluetooth®, WiFi
Expansion slot	Micro SD Card (SDHC) 128GB
Touch-screen panel	capacitive multi-touch
Indicators	Red/Green light
Communication interface	USB type C, OTG supported
Operating system	Android
Memory	3GB RAM, 32GB Flash
CPU Type	Qualcomm SDM450 1.8 GHz octa-core
Display type	4" WVGA Multi-touch capacitive display
WLAN Features	IEEE 802.11 a/b/g/n/r/ac radio
WPAN Features	Bluetooth Class 4.2
Operation interface	Volume up/down, left/righ scan, power, reset
Optical	
Camera	with LED flash, 13 MPix, with Autofocus
Bar code scanner	N6703 Standard Range
Electrical	
Main battery pack	Extended: Li-Ion 7000 mAh, 3,7V
Battery charging time	5.5hod
Main battery pack operating time	25hod
Mechanical	
Dimensions	Width: 78mm, Height: 206mm Length: 41.9mm
Weight	435g
Environment	
Electrical static discharge	±8kV contact, ±12kV air
Shock resistance	1000 tumbles at 1 m, multiply drops from 1,5 m onto concrete surface
Operating temperature	-20 to 50°C
Operating humidity (non-condensing)	10 to 90%

CODEWARE, s.r.o. Jaromírova 484/37

Ingress protection

120 00 Praha 2 - Nusle IČ: 61061395, DIČ: CZ61061395

+420 222 562 444 codeware@codeware.cz https://www.codeware.cz/



IP65

