

Honeywell®

Stratos 2421 Scanner Only, 399mm, Diamonex Platter

Honeywell's Stratos® 2400 5-sided, 360°-bioptic scanner increases productivity in demanding, high-volume seated environments where shorter vertical towers are required, and poor quality and highdensity bar codes are prevalent. Independent scanning planes and a modular design lower maintenance costs and ensure continuous operation.

The Honeywell Stratos 2421 offer pre-aligned optical scanning modules, and independent scanning planes which enable the scanner to maximize uptime and maintain productivity.



The scanner maximizes return on investment with analytical tools.

Stratos tools:

- **StratosSYNCTM Independent Scanning Planes:** Maintains productivity and uptime via independent scanning planes
- **StratosSCHOOL Operator Training Software:** Improves productivity and promotes safer scanning techniques
- **StratosSWAPTM Pre-Aligned Optical Scanning Modules:** Minimizes downtime and lowers the cost of service via modular optical scan engines
- **StratosSTATS Productivity Analytical Software:** Provides data critical to maintaining checkout productivity
- **Remote MasterMindTM Scanner Management Software:** Offers a quick and convenient solution for IT administrators seeking to manage all scanners within their network from a single remote location



Technical Description

Functionality & Operation

1D Barcode Symbolologies	All standard one-dimension barcodes, GS1-DataBar
--------------------------	--

Communication interface	RS232
-------------------------	-------

Optical

Scanning rate	5400 scans/sec
---------------	----------------

Resolution	4,5 mil (0,114 mm)
------------	--------------------

Light source	visible laser diode VLD 650 nm
--------------	--------------------------------

Bar code scanner	Laser
------------------	-------

Depth of scan field	H: 0 mm - 100 mm, V: 0 mm - 216 mm - 0,33 mm (13 mil) bar code
---------------------	--

Minimum symbol contrast	35%
-------------------------	-----

Scannig pattern	54 lines (38 lines horizontal, 16 lines vertical)
-----------------	---

Mechanical

Dimensions	Width: 292mm, Height: 130mm Length: 399mm
------------	---

Environment

Operating temperature	0 to 40°C
-----------------------	-----------

Storage temperature	-40 to 60°C
---------------------	-------------

Operating humidity (non-condensing)	5 to 95%
-------------------------------------	----------

CODEWARE, s.r.o.

Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

