CODEWARE
no more searching

OPTICON

L-22X 1D / 2D reader with stand, USB

The L-22X is a fast 2D imager that scans at a fast speed of 100 frames per second. The scanner is lightweight and ergonomically designed so it balances perfectly in your hand.

The L-22X is a welcome addition to our cabled scanners product range. The 2D image scanner has a modern design, scans at a speed of 100 fps and is designed to balance perfectly in your hand. As a result the scanner delivers a comfortable scan experience.



The L-22X is a cabled scanner that scans both 1D and 2D at a fast speed. Therefor this scanner is very suitable for retail and service tasks, like a check-out counter or on a service desk. This scanner is also used in some postal appliances, warehouses and healthcare business processes.

The L-22X is a fast 2D imager that scans at a fast speed of 100 frames per second. The scanner is lightweight and ergonomically designed so it balances perfectly in your hand.Furthermore, the cabled scanner comes with USB or RS-232 and in either black or white. The black or white combined with the sleek design will make sure that the scanner will look good on any counter or service desk.

In addition, the device is delivered with a stand that activates the auto-trigger enabling hands free scanning action. Moreover the device is sealed up to IP42 and is resistance to drop of 1.5 meters onto a concrete floor.

Features

- 1D & 2D scanning at 100 fps
- Ergonomic design
- Auto trigger modus
- Delivered with stand
- Can read up to 4 codes at a time, according to the settings

Unboxing Opticon L22X:

YOUTUBE='WSk7AaBvg1I'



Technical Description

Functionality & Operation	
Communication interface	USB
1D Barcode Symbologies	All standard one-dimension barcodes
2D Code Symbologies	all standard 2D-Codes
Optical	
Scanning rate	100scan/s
Electrical	
Power Source	+5V ±10%
Mechanical	
Color	black
Body housing	ABS plastic
Weight	150g
Dimensions	Width: 62.2mm, Height: 165.3mm Length: 31.4mm
Environment	
Storage temperature	-30 to 60°C
Operating humidity (non-condensing)	0 to 90%
Storage humidity (non-condensing)	0 to 90%
Maximal ambient light	100000lux
Operating temperature	-5 to 50°C
Ingress protection	IP42
Shock resistance	drop from 1,5 m onto concrete surface
Vibrations resistance	10-100 Hz with 2G for 1h.
Others	
Bundled Accessories	stand, power supply
Certifications	CE, FCC, VCCI, RoHS



CODEWARE, s.r.o.
Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
https://www.codeware.cz/