

Zebra MC3190-Z Industrial mobile computer, laser, RFID, Wi-Fi, QVGA, WEH, pistol

Motorola MC3190-Z is the mobile, industrial terminal provides not only barcode scanner, but thanks to RFID reader integreeritud and exceptional performance and the ability to read RFID tags in any position. The terminal is the perfect combination of high performance, ergonomic design and favorable price. This is particularly suitable for efficient condition monitoring of goods and assets such as inventory. In offices, shops or healthcare.

Motorola MC3190-Z is a new addition in the family of Motorola products, allowing the use of RFID technology in the UHF band, which is used in Europe 860 MHz frequency. This is the smallest and lightest mobile terminal with RFID reader and patented MAX RFID antenna design in hand. Of course there is a simple usability in retail, wholesale or industry. Pistol performance and lower weight predispose this model to the widest range of applications for RFID.



Main Features of the Motorola MC3190-Z:

- reading RFID tags
- robust construction
- universal use
- high performance
- patented MAX RFID antenna
- Longlife batte



Technical Description

Functionality & Operation	
Communication interface	USB, RS232
1D Barcode Symbologies	All standard one-dimension barcodes
Memory	256MB DRAM, 1GB Flash
Display type	3" QVGA color, with backlight
Operating system	Windows® Embedded Handheld
Keyboard	48 keys, alphanumeric
RFID transponder protocols	EPC Gen 2
Frequency	UHF: 865 - 868 MHz (EU)
Touch-screen panel	Yes
WLAN Features	IEEE 802.11 a/b/g/n
Antennas, Antenna inputs	integrated RFID antenna
WPAN Features	Bluetooth® Class II v2.1 EDR

Optical	
Resolution	320x320 px
Bar code scanner	Laser

Electrical	
Main battery pack	Extended: Li-Ion 4400 mAh, 3,7V

Mechanical	
Dimensions	Width: 162.6mm, Height: 119.4mm, Length: 193.4mm
Weight	650g

Environment	
Operating temperature	-10 to 50°C
Storage temperature	-30 to 70°C
Shock resistance	drop from 1,2 m onto concrete surface
Storage humidity (non-condensing)	5 to 95%
Operating humidity (non-condensing)	5 to 95%
Electrical static discharge	±8kV contact, ±15kV air
Ingress protection	IP54

CODEWARE, s.r.o.
Jaromirova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
+420 737 274 952
codeware@codeware.cz
<https://eshop.codeware.cz/>

