

OPTICON

NLV-3101 Fixed Barcode & 2D Code Imager, RS232

Opticon NLV 3101 is fixed barcode and 2D codes scanner, which is among the smallest device of its kind, excels with scanning rate of up to 60 scans per second. NLV 3101 is suitable for the most demanding applications, for example - is able to capture despite the scratched plexiglass.

Opticon awards the user with a free worldwide accessible setup tool as an addition to the standard way of setting up the device using printed barcode manual.



The NLV3101, a 2D CMOS fixed mount imager, quickly and efficiently scans 1D and 2D barcodes. This scanner is ideal for retail or industrial barcode scanning applications. The NLV3101 features red LEDs to illuminate the viewable area and green LEDs to precisely target the barcode to be scanned. Additionally, this fixed mount scanner has picture-capture capability: scanned images can be viewed to assist with troubleshooting in industrial applications.

The NLV3101 product highlights include:

- World's most compact 2D imager in its class
- Rapidly scans/decodes a wide variety of 1D or 2D barcodes
- Fast global shutter technology with adjustable illumination – easily scan any surface
- Exceptional motion tolerance for moving applications
- Improved scanning of curved, wide and poorly printed barcodes
- Green LED targeting function providing laserfree aiming with no laser class required
- Programmable with image capture software available
- Complete unit with integrated decoder
- USB (HID and VCP/COM), RS232 or keyboard wedge interface selectable
- Low power consumption provides design flexibility
- Rugged – IP65 rating for water and dust protection and shock resistant



Technical Description

Functionality & Operation

Communication interface	keyboard, RS232, USB
1D Barcode Symbolologies	All standard one-dimension barcodes
2D Code Symbolologies	Aztec, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code

Optical

Curvature	R>16 mm (10-digit Codebar), R>20mm (12-digit Codebar)
Depth of scan field	55-295 mm
Scanning rate	100scan/s

Mechanical

Weight	30g
Dimensions	Width: 24mm, Height: 41mm Length: 33mm
Body housing	ABS plastic

Environment

Storage temperature	-20 to 60°C
Storage humidity (non-condensing)	20 to 90%
Shock resistance	drop from 0,75 m onto concrete surface
Ingress protection	IP65
Operating humidity (non-condensing)	20 to 85%
Operating temperature	-20 to 50°C

Others

Certifications	CE, FCC (Class B), RoHS, VCCI
Warranty	1 year

CODEWARE, s.r.o.
Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

