

Honeywell®

PC42t - thermal transfer printer, 203dpi, USB, RS232, LAN

Easy to install, friendly price and ease of use makes the printer Honeywell PC42t ideal companion when printing bar codes, especially in manufacturing, healthcare and logistics.

New, efficient and economical printer Honeywell PC42t with the possibility of printing on media up to a width of 110 mm Ribbon length up to 300 meters (saving up to 30% compared to the competition). This printer is suitable for printing in low volume applications.



Key features of the printer Honeywell PC42t:

- compact size
- ease of installation
- cost-friendly
- intuitive easy media loading
- 64 MB Flash Memory 64 MB SDRAM
- communication interfaces: USB, USB host, Ethernet and serial

Video:

YOUTUBE='UYYNsgHzr4U'



Technical Description

Functionality & Operation

Print mode	direct thermal, thermal-transfer
Memory	64MB Flash
Memory	64MB DRAM
2D Code Symbolologies	all standard 2D-Codes
Maximal print width	104mm
Operation interface	1x button
Communication interface	USB
1D Barcode Symbolologies	All standard one-dimension barcodes
Commands set	TSPL-EZ
Print resolution	203dpi
Print speed	102mm/sec (4 ips)

Electrical

Power Source	100-240V, 50-60Hz
--------------	-------------------

Mechanical

Body housing	double-walled plastic
Color	black
Dimensions	Width: 226mm, Height: 177mm Length: 297mm
Weight	2.5kg

Consumables

Max. ribbon length	300m
Ribbon core diameter	12.7mm
Maximal paper width	110mm
Maximal roll diameter	127mm
Max. ribbon diameter	68mm
Ribbon width	25.4 to 109.2mm
Media core diameter	25.4 to 38.1mm
Minimal paper width	25.4mm
Minimal label length	9.6mm

CODEWARE, s.r.o.

Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

