

Honeywell®

PC42t - thermal transfer printer, 203dpi, USB, RS232, LAN

Easy to install, friendly price and ease of use makes the printer Honeywell PC42t ideal companion when printing bar codes, especially in manufacturing, healthcare and logistics.

New, efficient and economical printer Honeywell PC42t with the possibility of printing on media up to a width of 110 mm Ribbon length up to 300 meters (saving up to 30% compared to the competition). This printer is suitable for printing in low volume applications.




Key features of the printer Honeywell PC42t:

- compact size
- ease of installation
- cost-friendly
- intuitive easy media loading
- 64 MB Flash Memory 64 MB SDRAM
- communication interfaces: USB, USB host, Ethernet and serial

Video:

YOUTUBE='UYYNsgHzr4U'



Technical Description

Functionality & Operation

Print resolution	203dpi
Print speed	102mm/sec (4 ips)
Maximal print width	104mm
Print mode	direct thermal, thermal-transfer
Memory	64MB Flash , 64 MB SDRAM
Operation interface	1x button
1D Barcode Symbolologies	All standard one-dimension barcodes
2D Code Symbolologies	all standard 2D-Codes
Communication interface	USB, USB Host, Ethernet, RS232
Commands set	TSPL-EZ

Electrical

Power Source	100-240V, 50-60Hz
--------------	-------------------

Mechanical

Weight	2.5kg
Dimensions	Width: 297mm, Height: 226mm Length: 177mm
Color	black
Body housing	double-walled plastic

Consumables

Max. ribbon length	300m
Max. ribbon diameter	68mm
Ribbon width	25.4 to 109.2mm
Maximal roll diameter	127mm
Minimal paper width	25.4mm
Maximal paper width	110mm
Media core diameter	25.4 to 38.1mm
Minimal label length	9.6mm
Ribbon core diameter	12.7mm

Environment

CODEWARE, s.r.o.
Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

