PowerScan PD9130, USB KIT

The PowerScan PD9130 linear imager is a corded device offering state-of-the-art performance in an industrial product. This linear imager introduces Datalogic's new and innovative scanning technology, implementing a green scanning line which has the same definition of a laser beam with all the benefits of a linear imager.

The PowerScan™ PD9130 scanner is the latest Datalogic corded industrial product. The green scanning line has been proven to be the most comfortable color solution for the operator's eyes. The PD9130 reader has been tested to withstand extreme environmental conditions and is suitable for the most rugged and demanding settings. The PD9130 reader is fully supported by Datalogic's Aladdin™ configuration program which provides a user-friendly interface for the start-up procedure and device programming. All models have multi-interface capabilities: RS-232, Keyboard Wedge and USB.



Key featured:

- Ergonomic shape provides hours of tireless data collection for the user
- Datalogic new scanning linear imager technology (green laser-like scanning line)
- Datalogic's 3GL technology for multiple good-read feedback
- IP65 rating and 2.0 m / 6.6 ft drop resistance
- built-in tether hook for suspended applications ensures workplace productivity

YOUTUBE='EiUlkNRZOcI'

Technical Description

Functionality & Operation	
Indicators	Beeper, Datalogic Thee Green Lights, Good Read Feedback, Datalogic 'Green Spot' on the Code, Dual Good Read LeDs
Communication interface	Multi-interface - RS232/KBW/USB
1D Barcode Symbologies	GS1-DataBar, UPC/EAN, ISBN/ISSN, Code 128, EAN 128, Code 39, Code 93, Codabar, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Code 11, MSI, Plessey, Code 32, Code 32, Codablock F, Datalogic 2 of 5, IATA Code, Follet 2/5
Optical	
Depth of scan field	2 - 230 cm
Resolution	2,5 mil
Minimum symbol contrast	15%
Bar code scanner	1D Imager
Light source	green LED
Electrical	
Power Source	440 mA, 4.5 V, 380 mA, 5 V, 75 mA, 30 V, Input: 4.5 - 30 VDC
Mechanical	
Dimensions	Width: 76mm, Height: 212mm Length: 110mm
Weight	340g
Environment	
Shock resistance	Withstands 50 drops from 2 m onto concrete surface
Electrical static discharge	±20kV air
Operating humidity (non-condensing)	0 to 95%
Ingress protection	IP65
Operating temperature	-20 to 50°C
Storage temperature	-40 to 70°C
Others	
Recommended software	Datalogic Aladdin™ available for download at no charge

CODEWARE, s.r.o.
Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
https://www.codeware.cz/

