



PowerScan PD9530 High Performance 5VDC, USB Kit (Kit inc. Scanner and Cable CAB-524.)

The Datalogic PowerScan 9530 is a cable reader with improved code reader technology for improved visibility, user-friendly and high IP65 industry protection.

Warehouses, logistic centers and manufacturing plants depend on speed and reliability when managing goods and tracking merchandise in order to improve efficiency while reducing costs. Datalogic's PowerScan™ PD9530 area imager, the latest generation of rugged 2D area imagers, is the perfect answer for these applications.



An intuitive and effortless scanning experience is the target of the PowerScan™ 9500 family. It combines omnidirectional reading capabilities, which is typical in all area imaging scanners, with outstanding optical characteristics. The result is a scanner that is able to read any kind of bar code, regardless of the orientation, from contact to over 1.0 m / 3.3 ft, depending on the bar code resolution. In addition, the PowerScan PD9530 area imager includes Datalogic's latest decoding software that guarantees snappy reading in any type of environment. Aim, trigger, decode: it is that simple!

User comfort is guaranteed because of the scanner ergonomics, consisting of the handle shape, a well-balanced weight and an intuitive aiming system, allowing the highest first-pass reading rate while reducing unnatural wrist movement or rotation which can tire any user during long shifts. Additionally, the PowerScan 9530 area imager uses a soft-pulsed white illumination light resulting in reduced flashes, which is very gentle on the eyes and less troublesome to the operator during scan-intensive applications.

The PowerScan PD9530 area imager is available in 2 different models to meet the specific needs of each customer. The PD9530-HP (High Performance) model is more versatile because of the advanced optics that combine high resolution bar code reading capability (up to 2.5 mils for linear codes) and wide angle image capture (A4 image size @ 25.0 cm / 0.8 ft), while maintaining an exceptional depth-of-field.

Key features:

- Snappy omnidirectional reading from contact to over 1 m
- Datalogic's new instinctive 'fraime' aimer
- New 'soft white light' illumination
- Datalogic's 3GL™ technology and loud beeper for good read feedback
- Datalogic's Motionix™ motion-sensing technology
- Water and Particulate Sealing Rating: IP65



Technical Description

Functionality & Operation

Communication interface	USB
1D Barcode Symbolologies	All standard one-dimension barcodes, UPCA, UPCE
2D Code Symbolologies	Aztec, Data Matrix, MaxiCode, Micro QR Code, QR code, MicroPDF417, PDF417, GS1 DataBar Composite Code

Optical

Depth of scan field	2 - 110 cm
Bar code scanner	2D Imager
Maximal skew angle	40°
Maximal pitch angle	40°
Resolution	2,5 mil 1D, 4 mil 2D
Minimum symbol contrast	15%

Electrical

Power Consumption - Operation	335mA
Power Source	+5 VDC ±10%
Power Consumption - Standby	180mA

Mechanical

Dimensions	Width: 212mm, Height: 110mm Length: 74mm
Weight	330g

Environment

Maximal ambient light	100000lux
Storage temperature	-40 to 70°C
Operating temperature	-20 to 50°C
Ingress protection	IP65
Electrical static discharge	±20kV air
Operating humidity (non-condensing)	0 to 95%
Shock resistance	Withstands 50 drops from 2 m onto concrete surface

Others

Bundled Accessories	Charging and Communication Cradle
Certifications	CE, FCC, RoHS, IEC 60925-1: Class 2, IEC 62471 Exempt

CODEWARE, s.r.o.
Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

