



PRP-003 Thermal Receipt Printer with autocutter, USB & RS232, black, print in Czech

Quiet, fast and powerful - and yet cost very effective. This is thermal printer PRP-003. POS Printer PRP-003 has a large 4MB input memory buffer and faster interfaces: USB 2.0, in the case of network model the Ethernet of 10/100 Base-T specification. It is equipped with a jack to open cash drawer and automatic cutter.





















Technical Description

Functionality & Operation

runctionality & Operation	
Communication interface	RJ-11 cash drawer port, USB, RS232
Print speed	220mm/sec (9 ips)
Print resolution	203dpi
Inter-dot space	0.125mm
Maximal print width	80mm
Fonts	Font A: 1.5x3 mm (48 columns)
Fonts	Font B: 1.13x2.13 mm (64 columns)
Fonts	ASCII: 13 international character sets
Commands set	ESC/POS
Print mode	direct thermal
Electrical	
Power Source	+24 VDC/2.5A
Mechanical	
Dimensions	Width: 200mm, Height: 145mm Length: 145mm
Weight	2kg
Consumables	
Maximal paper width	80mm
Maximal roll diameter	80mm
Paper thickness	53 to 80g/m2
Environment	
Storage humidity (non-condensing)	10 to 90%
Storage temperature	-20 to 60°C
Operating humidity (non-condensing)	10 to 80%
Operating temperature	0 to 50°C

CODEWARE, s.r.o. Jaromírova 484/37

120 00 Praha 2 - Nusle IČ: 61061395, DIČ: CZ61061395

+420 222 562 444 codeware@codeware.cz https://www.codeware.cz/



