

PRP-F03 Thermal Receipt Printer with autocutter, USB & RS232, black

Fast and powerful POS printer Birch BP-F03BR with a ceramic knife and a front opening for easy introduction of paper roll. The knife guarantees 1.8 million cuts. It is characterized by memory size of 4MB and a print speed of 300 mm / second. It fits in very demanding environments where users need fast and trouble-free printing. It supports printing barcodes and connection via USB 2.0 and RS232.

Key Features Birch BP-F03:



- Front-open printing with easy-paper-loading device, could let you put the printer to the height limited space.
- Built-in " Ceramic cutter " with long working life 1.8 million times" ceramic knife always be sharp, more reliable and durable .
- High speed and 100M Wifi distance in open space, long distance for easy printing anywhere.
- Multi-functional and high performance, changeable interface could conquer any application, QR code and NV logo printing support.
- 300 mm / second print speed with 4M input buffer, it's means that BP-F03 could provide you a high speed printing and wouldn't miss any printing file.



Technical Description

Functionality & Operation

| | |
|--------------------------|---|
| Print resolution | 203dpi |
| Communication interface | RJ-11 cash drawer port, USB, RS232 |
| 1D Barcode Symbolologies | UPCE, UPCA, EAN 13/UPCA, Code 128, Code 39, Codabar |
| 2D Code Symbolologies | PDF417, QR code |
| Input buffer | 4MB |
| Print mode | direct thermal |
| Print speed | 300mm/sec (12 ips) |
| Maximal print width | 79mm |
| Commands set | ESC/POS |

Optical

| | |
|---------|---|
| Sensors | ribbon end sensor, open print-head detector, reflective, transmissive |
|---------|---|

Electrical

| | |
|--------------|--------|
| Power Source | 24 VDC |
|--------------|--------|

Mechanical

| | |
|------------|---|
| Dimensions | Width: 142mm, Height: 132mm Length: 195mm |
| Weight | 1.5kg |
| Color | black |

Consumables

| | |
|-----------------------|-----------------|
| Maximal roll diameter | 83mm |
| Media thickness | 0.065 to 0.14mm |
| Maximal paper width | 80mm |

Environment

| | |
|-------------------------------------|-------------|
| Operating temperature | 5 to 35°C |
| Storage temperature | -40 to 55°C |
| Storage humidity (non-condensing) | 10 to 93% |
| Operating humidity (non-condensing) | 25 to 80% |

Others

| | |
|----------|--------|
| Warranty | 1 year |
|----------|--------|

CODEWARE, s.r.o.
Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

