

SCR-5200 Smart Cards Reader, USB, black

reader/writer for SMC smartcards, EMV level 1 compliant, uses Microsoft CCID native driver, supports PC/SC driver for Windows, Linux, WinCE

Main Features

USB Interface Insert Read / Write Smart card EMV level 1 compliant Support PC/SC driver for Windows, Linux, WinCE Driver and utilities are provided

Applicatio

n P.O.S

. Banking & Payme

nt E-Comme

rce Security & Identification, Access Con

tr

ol F

eatures St

andard: ISO7816, EMV, GSM, PC/SC,

and WHQL CCID speci fications USB spe

cification Host Interface: Full speed USB 1.1 / 2.0 with CCID protocol Host Connector: USB type A Smart Ca

rd Interface : Automatic recognize and access 5V/3V/1.8V (Class A, B, C) smart card Access 2-wire: SLE4432, SLE4442 ; 3-wire: SLE4418, SLE4

428 memory card Short-ci

rcuit protection Reads from and Writes to all ISO7816-1/2/3 microprocessor c ards, T=0 and T=1 Wide range communication baud rate up to 11.625 clock p

ulses (D=32/F=372) Support functions of S-blo

ck: WTX, Abort, IFS S

mart Card Connector: 8 frictions contacts ISO loca

tion, Landing Contact 30

0,000 insertion cycles EMV level 1

mechanically compliant Emboss

ed smart cards supported LED indicato

r Supported PC/SC Driver :

Windows 9

8, ME, 2

000, XP WinCE.Net Linux Other OS su

pported upon request (MacOS X) Dimension (L*W*H): 110 x 37 x 44 (mm) Cable Length: 1500

(mm) Environmental Performances : Op erating temperature: +0°C to +65°C



Technical Description



+420 222 562 444 codeware@codeware.cz https://www.codeware.cz/



