

DA200 Desktop Direct Thermal Bar Code Printer, no SD-card slot, 5 ips, 203 dpi, USB+LAN

Desktop Barcode Printer DA200 / DA300 from TSC has all the good qualities sought customers for small printers. It's lightweight, easy to carry, takes up little space, quiet and easy to operate. Yet delivers the performance expected by the middle class Label Printer: big memory for handling complex formats and high printing speed. In short, these printers are ideal combination of established quality, performance and affordability.

Printer TSC DA200 / DA300 redefines value-frills desktop printers labels. Although the cost of the printer itself is low, it looks like and has better performance than expensive competitor models.



Printer DA200 / DA300 can print on various types of labels - labels ranging from shipping through the usual stickers for labeling and identification of goods to labels and tickets. Labels may not always be paper. In factories of industrial enterprises, for recording automobile parts, etc., are frequently used labels from polyethylene, datapol, possibly from other materials. Characterized by easy media loading.

TSC printers have the Thermal Smart Control technology, a patented electronic print head temperature control. Print output is sharper because of that technology and, what's even more important, printhead life is several times longer.

Main features of the printer DA200 / DA300:

- easy media loading
- High memory - 64 MBSRAM, 128 MB Flash
- small size
- print speed of up to 127 mm / sec
- USB 2.0, RS-232, Ethernet
- 32-bit RISC processor
- print resolution up to 300 DPI
- Smart Thermal Control technology significantly extends printhead life and ensures sharper print output

3'

Loading the me

dia: YOUTUBE='LrGVUo



1D CODE



2D CODE



ETHER



USB



NO CABLE



203
DPI



DT
PRINTER

Technical Description

Functionality & Operation	
Maximal print length	2286mm
Maximal print width	108mm
Print speed	127mm/sec (5 ips)
Print resolution	203dpi
	127mm
Print mode	direct thermal
CPU Type	32-bit RISC
Communication interface	USB, RS232
Fonts & barcode rotation	0°, 90°, 180°, 270°
1D Barcode Symbologies	All standard one-dimension barcodes
2D Code Symbologies	Data Matrix, MaxiCode, QR code, Aztec, PDF417, MicroPDF417
Indicators	LED (green, amber & red)
Fonts	8 alpha-numeric bitmap fonts,Monotype Image ® true type font engine with one CG Triumvirate Bold Condensed scalable font
Commands set	TSPL-EZ TM (Compatible to EPL, ZPL, ZPL II) or CPCL emulation
Optical	
Sensors	ribbon end sensor, open print-head detector, transmissive, reflective
Electrical	
Power Source	External universal switching power supply, Input: AC 100-240V, 1A, 47-63HZ, Output: DC 24V, 2.5A 60W
Mechanical	
Weight	1.3kg
Dimensions	Width: 172mm, Height: 165mm Length: 195mm
Body housing	double-walled plastic
Consumables	
Maximal paper width	114mm
Media type	continuous, black-marked media, fan-fold, notch, thermal labels
Media core diameter	25.4 to 38mm
Media thickness	0.055 to 0.19mm
Minimal paper width	19mm
Environment	
Operating temperature	5 to 40°C
Storage temperature	-40 to 60°C
Operating humidity (non-condensing)	25 to 85%
Storage humidity (non-condensing)	10 to 90%
Others	
Certifications	RoHS, WEEE
Warranty	2 years (printer), 25000 m or 12 months (print head), 50000 m or 12 months (printing cylinder), approved material CODEWARE
Bundled Accessories	quick start guide, USB cable, power cord, CD Windows software

Optional accessories

Bluetooth, KP-200 Plus keyboard display unit, KU-007 Plus smart keyboard, cutter, RTC - real time clock, dispenser kit

CODEWARE, s.r.o.

Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

