

MX340P Metal Industrial Bar Code Printer, 300 dpi, 14 ips

TSC MX240P / MX340P / MX640P series of industrial barcode printers features excellent performance and high durability. The printer is designed for demanding users who would not accept any compromise. Barcode printer TSC MX-series can instantly replace any most competitive products thanks the native emulation of command languages Zebra, Eltron, Datamax and Sato. The TSC MX printer achieves higher performance and easier operation for a lower cost. TSC MX240P / MX340P / MX640P can be equipped with a cutter, dispensator, internal rewinder and RFID encoder (HF or UHF).

Just at the first sight of the printer you will certainly be attracted by large color touch panel on the front, which makes the operation much more variable and more convenient than using the buttons. However, the MX240P can also be operated in a standard way - under the touch screen there are 6 buttons (Menu, Pause, Feed, Up, Down, and Select).



Despite its size, the MX240P industrial bar code printer is relatively light - both internal mechanism and external housing are aluminum die castings. Precisely designed print mechanism enables fast print at almost half meter per second, even of the very small labels (3 mm) with a 600 m long ribbon, no matter of if the ink is IN or OUT, 24 hours x 7 days without interruption. Time savings acquired from high printing speed are even magnified by the ingeniously designed print mechanism, which enables replacement of media as quickly as possible and without such problems like wrinkled ribbon or necessity of adjusting the labels to the correct line.

All the TSC bar code printers of series MX240P are equipped with RS232, USB and Ethernet interfaces and in addition they have a slot for SDHC memory card. Additionally, your printer may be also equipped with wireless interface Bluetooth or WLAN.

TSC printers have the Thermal Smart Control technology, a patented electronic print head temperature control. Print output is sharper because of that technology and, what's even more important, printhead life is several times longer.

Thanks to the automatic recognition and the instant emulation of any of the mostly used barcode printers command sets (ZPL2 - Zebra, EPL2 - Eltron, DPL - Datamax and SBPL - Sato) is the TSC MX240P printer easy to integrate into almost any of the user systems.

Key features of the TSC barcode printer MX240P / MX340P / MX640P

- high print speed at 18 ips / 14 ips / 6 ips;
- powerful 32-bit processor, 536 MHz multitasking;
- 600 m ink ribbon with ink IN or OUT;
- color touchscreen control panel;

- ruggedness and settings stability thanks the print mechanism and housing made from aluminum die cast;
- automatic emulation of ZPL2, EPL2, DPL and SBPL on the fly, without need for manual switching;
- large memory of 512 MB Flash + 512 MB SDRAM + slot for SDHC memory card;
- RS232, USB and Ethernet interfaces as standard;
- optional wireless interface Bluetooth or WLAN;
- Smart Thermal Control technology significantly extends printhead life and ensures sharper print output
- optional module for encoding of and concurrent printing on RFID labels, either HF (13.56 MHz) or UHF (860 MHz - 930 MHz).

[See the product video on Youtube](#)



Technical Description

Functionality & Operation

Print speed	356mm/sec (14 ips)
Maximal print length	11430mm
Communication interface	Ethernet, RS232, USB, USB Host
Print resolution	300dpi
Display type	4,3" LCD color
Expansion slot	SD Card (SDHC)
Indicators	3xLED
Maximal print width	104mm
Memory	512MB DRAM
Memory	512MB Flash
Operation interface	color touch LCD panel, 7x button
Print mode	direct thermal, thermal-transfer
Touch-screen panel	Yes
1D Barcode Symbologies	All standard one-dimension barcodes
2D Code Symbologies	all standard 2D-Codes
Commands set	TSPL-EZDS

Optical

Resolution	480x272 px
Sensors	open print-head detector, reflective, ribbon end sensor, transmissive, TT ribbon detector

Mechanical

Weight	18kg
Dimensions	Width: 510mm, Height: 300mm Length: 393mm
Body housing	aluminium
Color	silver

Consumables

Ribbon core diameter	25.4mm
Ribbon width	40 to 115mm
Max. ribbon length	600m
Maximal paper width	104mm
Ink of TT ribbon	ink-side IN, ink-side OUT
Maximal roll diameter	203mm
Media type	black-marked media, continuous, datapol, fan-fold, notch, paper and thermal-paper labels, perforated, polyethylen, Roll-feed, tags, textile ribbon, thermal labels, tickets
Minimal label length	3mm
Minimal paper width	20mm
Media core diameter	76.2 to 76.2mm
Media thickness	0.076 to 0.305mm

Environment

Storage humidity (non-condensing)	10 to 90%
Storage temperature	-40 to 60°C
Operating temperature	5 to 40°C
Operating humidity (non-condensing)	25 to 85%
Others	
Warranty	2 years (printer), 25000 m or 12 months (print head), 50000 m or 12 months (printing cylinder), approved material CODEWARE
Certifications	C-Tick Class B, CCC, CE Class B, cUL, FCC (Class B), TÜV/Safety, UL

CODEWARE, s.r.o.
Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

