

## TDP-244 Desktop, Plastic, Clamshell design DT, 203 dpi, 4 ips

Desktop Barcode Printer TSC- TDP 244 has all the qualities sought customers for small printers. It is lightweight, portable, durable and very favorable price. He also offers parameters that are projected for the middle class printers: print speed of 102 mm / s (4 ips), easy media loading, price performance ratio and easy connection.

Company TSC is a traditional manufacturer of barcode printers, one of them is a direct thermal printer TDP 244. This printer offers the ideal combination of low prices, vyysoké print quality, long life and high reliability. Despite its small size offers high performance that customers have come to expect TSC printers. It is suitable for retail or offices. It is the successor of one of the best selling printers in this class TSC TDP 245. It is fully compatible with the command sets Eltron and Zebra.



TSC printers have the Thermal Smart Control technology, a patented electronic print head temperature control. Print output is sharper because of that technology and, what's even more important, printhead life is several times longer.

### Basic features of barcode printers TDP 244:

- easy media loading
- High Speed USB 2.
- print resolution 203 dpi - print speed of 102 mm / s (4 ip)
- Smart Thermal Control technology significantly extends printhead life and ensures sharper print output
- low purchase price
- memory 8 MB DRAM, 4 MB Flash
- SD expansion card
- large power supply 60W



# Technical Description

## Functionality & Operation

Print mode	direct thermal
Print resolution	203dpi
Print speed	102mm/sec (4 ips)
1D Barcode Symbolologies	Code 39, Code 93, Code128UCC, Code 128 subset A.B.C., Codabar, Interleaved 2 of 5, EAN 8, EAN 13, EAN 128, UPCA
Operation interface	1x button
Maximal print width	108mm
Maximal print length	2286mm
Fonts & barcode rotation	0°, 90°, 180°, 270°
2D Code Symbolologies	PDF417, MaxiCode, Data Matrix, QR code
Fonts	8 alpha-numeric bitmap fonts, Monotype Image ® true type font engine with one CG Triumvirate Bold Condensed scalable font
Commands set	TSPL-EZ TM (Compatible to EPL, ZPL, ZPL II) or CPCL emulation
Memory	4MB Flash , 8 MB SDRAM

## Optical

Sensors	ribbon end sensor, open print-head detector, transmissive, reflective
---------	---

## Electrical

Power Source	External universal switching power supply, Output: DC 24V, 2.5A 60W, Input: AC 100-240V, 1A, 47-63HZ
--------------	--

## Mechanical

Weight	1.9kg
Dimensions	Width: 240mm, Height: 200mm Length: 164mm
Body housing	double-walled plastic

## Consumables

Media thickness	0.06 to 0.16mm
Maximal paper width	112mm
Minimal paper width	20mm
Media type	black-marked media, continuous, fan-fold, perforated
Media core diameter	25.4 to 76.2mm
Maximal roll diameter	127mm

## CODEWARE, s.r.o.

Jaromírova 484/37  
120 00 Praha 2 - Nusle  
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444  
codeware@codeware.cz  
<https://www.codeware.cz/>

