

TX200 Desktop Barcode Printer, 203 dpi, 8 ips, USB + RS232 + LAN, int. slot for BT/WF

Series thermal transfer barcode printers TSC TX-200 / TX-300 / TX-600 has all the positive qualities sought customers for small desktop printers. The printer is lightweight, portable, silent, high performance, takes up little desk space, well controlled and at unbeatable offers price. Simultaneously parameters above expectations for middle-class printers, just 300m ribbon, high memory up to 128 MB-highest in class, very easy media loading, or print speed up to 203 mm / s (8 ips).

The new generation of thermal transfer desktop printers from TSC. It supports multiple print applications than any other printer in its class. TSC saving printer will save you not only time, but also money. The printer is made from high quality, durable materials in a timeless design. Although the cost of the printer itself is low, looks similar and has better performance than expensive competitor models. Design criteria printer friendly form provides a simple media loading. With the expansion SD Flash Card reach incredibly high memory. Thanks to its small size, the printer is also suitable for smaller spaces in offices, healthcare, shipping, tracking, etc ..



TSC printers have the Thermal Smart Control technology, a patented electronic print head temperature control. Print output is sharper because of that technology and, what's even more important, printhead life is several times longer.

Printer TX-200 is available in the following models: - TX-200 with print speeds up to 8 ips (203 mm / s) and a print resolution of 200 DPI - TX-300 with print speeds up to 6 ips (152 mm / s) and a print resolution of 300 DPI - TX-600 with print speeds up to 4 ips (102 mm / s) and a print resolution of 600

D

PI The main characteristics of a thermal transfer printer TSC T

X-

- 200: possibility of 300 dpi and 600 dp
- i models very high memory 128 MB Flash, 128
- MB SDRAM micro SD Flash memory expansion u
- p to 32 GB 32 bit RI
- SC procesor easy m
- edia loading print speed of up to 203 m
- m / s (8 ips) 3.5 " TFT LCD display with standard-TX-600, optional
- on TX-200/300 Smart Thermal Control technology significantly extends printhead life and ensures sharp
- er print output Firmware TSPL-EZ™ s automatic emulation TPLE (Translation Printer Language Eltron®) and TPLZ (Translation Printer
- Language Zebra®) ribbon

- up to 300 meters communication interface
- Ethernet, USB 2.0 user-friendly
- ly clamshell design
- n 2 years warranty durab

il

ity and reliability

Loading the media:

YOUTUBE=v

sThGsyHDZE' Unboxin



Technical Description

Functionality & Operation

Expansion slot	SD Card (SDHC), for wireless BT/WiFi connection
Maximal print length	25400mm
Maximal print width	108mm
Operation interface	LED panel with 8 big icons, 2x button
Print speed	203mm/sec (8 ips)
Print resolution	203dpi
Memory	128MB DRAM
Memory	128MB Flash
Fonts & barcode rotation	0°, 90°, 180°, 270°
Commands set	TSPL-EZ TM (Compatible to EPL, ZPL, ZPL II) or CPCL emulation
Print mode	thermal-transfer
CPU Type	32-bit RISC
Communication interface	USB Host, Ethernet, USB, RS232
Fonts	8 alpha-numeric bitmap fonts, Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font
1D Barcode Symbologies	All standard one-dimension barcodes
2D Code Symbologies	TLC-39

Optical

Sensors ribbon end sensor, open print-head detector, transmissive, reflective

Electrical

Power Source 100-240V, 50-60Hz

Mechanical

Weight 3.75kg

Dimensions Width: 226mm, Height: 198mm Length: 332mm

Body housing double-walled plastic

Consumables

Minimal label length 3mm

Maximal roll diameter 127mm

Max. ribbon length 300m

Ribbon width 40 to 110mm

Media type black-marked media, continuous, fan-fold, notch, perforated

Media core diameter 25.4 to 38.1mm

Minimal paper width 19mm

Maximal paper width 112mm

Media thickness 0.055 to 0.254mm

Environment

Operating temperature 5 to 40°C

Storage temperature -40 to 60°C

Operating humidity (non-condensing) 25 to 85%

Storage humidity (non-condensing) 10 to 90%

Others

Optional accessories Bluetooth, Centronics Parallel, KU-007 Plus smart keyboard, RTC - real time clock, cutter, Wi-Fi, KP-200 Plus keyboard display unit, dispenser kit

Warranty 2 years (printer), 25000 m or 12 months (print head), 50000 m or 12 months (printing cylinder), approved material CODEWARE

Bundled Accessories power cord, USB cable, quick start guide, CD Windows software

Certifications RoHS, WEEE, FCC (Class B), CE Class B, RCM, UL, cUL, CCC, TÜV/Safety

CODEWARE, s.r.o.

Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

