



Z-3060 Omnidirectional handheld laser bar code scanner with stand, RS232, black

Do you miss the old good Metrologic MS6720? Zebex Z-3060 is exactly such a cash-out omni-directional bar code scanner! The Z-3060 is a more cost-effective alternative to the Honeywell MK6720 Fusion.

With stylish exterior and great flexibility, the Z-3060 is versatile in all applications. Dreamed of having omnidirectional and single-line scanning capabilities in one scanner and yet not compromising the size? The answer is Z-3060, a handheld scanner on an adjustable stand. Whenever scanning small items or large bulky items, on the counter or off the counter, and by handheld or hands-free, the Z-3060 fulfills all kinds of operating needs. The Z-3060 has a scan rate of 1 400 per second and also boasts 20 line laser scan pattern.



Key Features:

- Support both omnidirectional and single-line scanning
- Aggressive scanning performance
- Proprietary Z-SCAN+ technology
- Rubber impact defensive front of the reading head



Technical Description

Functionality & Operation

Communication interface	RS232
Indicators	Three-color LED , programmable tone and volume
1D Barcode Symbolologies	UPC/EAN/JAN, UPCA, UPCE, EAN 13, EAN 8, ISBN/ISSN, Code 39, Codabar, Code 128, EAN 128, Code 93, IATA Code, MSI, China Postal Code, Industrial 2 of 5, Standard 2 of 5, JAP, Code 11, GS1-DataBar, GS1 DataBar Limited, GS1 DataBar Expanded JAN-8, JAN-13, ITF 2 of 5, Code 32

Optical

Light source	visible laser diode VLD 650 nm
Depth of scan field	0-280 mm
Scannig pattern	5 directions
Scanning rate	1400scans/s omnidirectional, 70scans/s single-line
Minimum symbol contrast	30% UPC/EAN 100%
Bar code scanner	Laser

Electrical

Power Source	+5 VDC \pm 10%, 200 mA
--------------	--------------------------

Mechanical

Dimensions	Width: 200.3mm, Height: 75.2mm Length: 68.4mm
Weight	190g , 460g with stand
Color	black
Cable lenght	2m

Environment

Operating temperature	0 to 40°C
Storage temperature	-20 to 60°C
Operating humidity (non-condensing)	5 to 95%
Maximal ambient light	4500lux
Shock resistance	drop from 1,5 m onto concrete surface

Others

Bundled Accessories	stand
Certifications	Laser Class: CDRH Class IIa, IEC 60825-1: Class 2, CE, EN 55022, FCC Part 15B, BSMI, VCCI

CODEWARE, s.r.o.
Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

