



Z-3192BT Wireless Bar Code, 2D and QR Code Scanner w. Cradle, USB, black

Of rugged form factor and supreme scanning performance, the wireless laser scanner Zebex Z-3192BT is able to work at a range up to 100M.

Its gun type design and large trigger allow users to aim at target easily; the ergonomic outline creates comfort in holding even for long hour. Along with ZEBEX advance decoding technology, the scanner is easy in operation and efficient in work, designed to benefit workers in all business sectors.



Product Highlights of the Zebex Z-3192BT Scanner

- Decodes most of the 1D & 2D barcodes
- Strong gun type design
- Smart battery charging design
- Flexible communication options
- Captures barcodes on mobile phone, tablet, or computer screens



Technical Description

Functionality & Operation	
2D Code Symbolologies	all standard 2D-Codes
WPAN Features	Bluetooth® Class I 2.4 GHz
Indicators	LED , (optional vibration), buzzer
Wireless communication	Bluetooth®
Bluetooth profiles	HID, SPP, Cradle host
Signal coverage	100m line sight distance
1D Barcode Symbolologies	Codabar, Code 11, Code 128, Code 32, Code 39, Code 93, GS1 Data Bar (RSS), Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, MSI, Plessey, Telepen, ISBN/ISSN, UPC/EAN/JAN, Standard 2 of 5, China Postal Code
Communication interface	JPOS, OPOS, Wand Emulation, USB-VCP, RS232, USB-HID, keyboard, TTL
Optical	
Depth of scan field	30~420 mm
Maximal skew angle	39.6°
Maximal pitch angle	25.7°
Maximal roll angle	360°
Minimum symbol contrast	30% UPC/EAN 100%
Resolution	5 mil, 752H×480V pixels
Scanning rate	60 scan/s
Bar code scanner	2D Imager
Light source	visible laser diode VLD 650 nm
Viewing angle	0 to 47°
Electrical	
Battery charging time	5hod
Main battery pack operating time	7hod
Power Source	+5V ±10%
Mechanical	
Dimensions	Width: 114.5mm, Height: 62mm Length: 147mm scanner only
Dimensions	Width: 133.6mm, Height: 101.6mm Length: 176.4mm with cradle
Weight	200g including battery
Color	black
Environment	
Shock resistance	drop from 1,2 m onto concrete surface
Operating temperature	0 to 50°C
Storage temperature	-20 to 60°C
Relative humidity (non-condensing)	5 to 95%
Maximal ambient light	100000lux
Ingress protection	IP41
Others	
Bundled Accessories	Charging and Communication Cradle

CODEWARE, s.r.o.

Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

